

EV 125 Vakuum

EV 125

Beschreibung / Description

EV 125 VAKUUMGebaut gemaess Richtlinie 89/392 EWG. Ausfuehrung EExd IIBT3-IP55. Geeignet fuer die Rueckgewinnung aller verschmutzter Loesungs- und Verduennungsmittel und fuer die Austrocknung der Rueckstaende. Doppelwandiger Loesemittelbehaelter und Vakuumbehaelter aus Chrom-Nickel-Stahl nach DIN 1.4301. Indirekte Heizung durch Diathermikoeel. Abkuehlung der Daempfe mittels Luft/Luft Austauschers. Rueckstandsentsnahme und Reinigung des Behaelters durch Raket, der von einem hydraulischen Motorangetrieben ist. Elektrische Vakuumpumpe, Saugvermoegen 4 m³/Std. Hoechstvakuum erreichbar 680 mm. Min.-max. Vakuumregler und Vakuummeter. Pneumatische Pumpe zum Foerdern des destillierten Loesungs-mittels eingebaut auf der Vakuumanlage.

EV 125 VACUUMManufactured according to directive 89/392/ EEC. Execution EExd IIBT3-IP55.

Suitable for recovering all exhausted solvents and thinners, and desiccation of residue waste. Double-walled solvent tank and vacuum tank in AISI 304 stainless steel. Indirect heating by diathermic oil. Vapour cooling by air/air condensing coil. Extraction of waste and cleaning of solvent tank by doctor blade driven by hydraulic motor. Electrical vacuum pump with 4 cu m/pH range. Maximum vacuum 680 mm. Minimum and maximum vacuum gauge. Pneumatic pump to transfer the reclaimed solvent installed on the vacuum system.

Technische Daten / Technical data

Kapazität / Capacity	125 lt.
Leistung Heizung / Heating power	9,6 kW
Zyklusdauer h / Cycle length h	4,5 - 8
Abmessungen / Dimensions	210 x 102 x 252 cm
Gewicht / Weight	1000 kg

* Änderungen und Irrtümer vorbehalten, alle Preise zzgl. Verpackung und Mwst.

Lösemitteldestillation

Languages > 

Lösemittel-Liste

LÖSEMITTEL	SIEDEPUNKT °C	SPEZIFISCHES GEWICHT bei 20°C	DAMPFDRUCK bei 20°C mm Hg	FLAMMPUNKT °C	RELATIVE FLÜCHTIGKEIT (ÄTHER=1)
Aceton	56,1	0,792	178	- 17	2,1
Äthylacetat	77	0,900	72,8	+ 2	2,9
Äthylalkohol	78	0,840	45	+ 14	8,3
Äthyläther	34-35	0,722	422	- 40	1
Äthylglykol	135	0,932	4,5	+ 40	43
Äthylglykolacetat	156,4	0,972	1,2	+ 49	47
Butylacetat n.	126,3	0,882	10	+ 25	11,8
Butylacetat sec.	112,2	0,870	-	+ 19	12
Butylalkohol	117	0,810	5	+ 46	33
Cyclohexan	81	0,783	3,1	- 12	5
Cyclohexanol	161	0,945	-	+ 68	103
Cyclohexanon	156	0,947	4	+ 54	40,4
Dekalin	180-190	0,890	-	+ 57	-
Dichloräthan	84-84	1,255	64	+ 21	-
Dichlorpropan	96,4	1,156	36	+ 21	-
Dimethylformamid	153	0,953	3,5	+ 57	-
Isobutylacetat	117	0,871	12,8	+ 18	7,7
Isobutylalkohol	107	0,805	8,8	+ 38	24
Isopropylacetat	89,4	0,869	63	0	4,2
Isopropylalkohol	82	0,786	32,9	+ 22	21
Methylacetat	57	0,932	170	- 13	2,2
Methylalkohol	65	0,792	96	+ 5,5	53
Methyläthylketon	78-85	0,820	65	+ 14	5,3
Methylenchlorid	40-42	1,323	349	unentflammbar	1,8
Methylglykolacetat	138	1,001	7,3	+ 44	35
Perchloräthylen	121	1,623	14	unentflammbar	11
Propylacetat	97-102	0,887	25	+ 12	6,1
Solvesso 100	157-180	0,88	4,1	+ 43	
Solvesso 150	183-210	0,9	0,3	+ 66	
Toluolo	109,5-110	0,866	22	+ 7	5,1
Trichloräthan 111	70-88	1,320	100	- 95	-
Trichloräthylen	87	1,464	56	unentflammbar	3,8
Xylol	137-139	0,854	10	+ 23	

* Änderungen und Irrtümer vorbehalten, alle Preise zzgl. Verpackung und Mwst.

Solvent distillation

Languages >  

Thinner and solvent list

THINNER AND SOLVENT	BOILING POINT °C	GRAVITY AT 20/4°C	VAPOUR TENSION AT 20°C IN mm	FLASH POINT °C	RELATIVE VOLATILITY
Aceton	56,1	0,792	178	- 17	2,1
Butyl acetate sec.	112,2	0,870	-	+ 19	12
Butyl acetate n.	126,3	0,882	10	+ 25	11,8
Butyl alcohol	117	0,810	5	+ 46	33
Butyl alcohol sec.	99,5	0,808	-	+ 24	20
Butylglycol	161-182	0,907	-	+ 60	-
Cyclohexane	81	0,783	3,1	- 12	5
Cyclohexanol	161	0,945	-	+ 68	103
Cyclohexanone	156	0,947	4	+ 54	40,4
Decalin	180-190	0,890	-	+ 57	-
Diacetonolcohol	150-165	0,938	10	+ 52	147
Dichlorethane	84-84	1,255	64	+ 21	-
Dichloropropane	96,4	1,156	36	+ 21	-
Diesel oil solvent	120-180	0,874-0,910	-	+ 22-32	-
Diethylenic glycol	240-250	1,120	-	+ 143	-
Dimethylformamide	153	0,953	3,5	+ 57	-
Dipentene	175-195	0,840-0,850	-	+ 43	-
Ethyl acetate	77	0,900	72,8	+ 2	2,9
Ethyl alcohol	78	0,840	45	+ 14	8,3
Ethyl ether	34-35	0,722	422	- 40	1
Ethylenic glycol	135	0,932	4,5	+ 40	43
Ethyl-glycol acetate	156,4	0,972	1,2	+ 49	47
Ethylsiliceous alcohol	183,5	0,830	0,05	+ 27	-
Freon 112	92,8				
Isobutyl acetate	117	0,871	12,8	+ 18	7,7
Isobutyl alcohol	107	0,805	8,8	+ 38	24
Isoforone	205-216	0,920	-	-	-
Isopropyl acetate	89,4	0,869	63	0	4,2
Isopropyl alcohol	82	0,786	32,9	+ 22	21
Methyl alcohol	65	0,725	96	+ 5,5	53
Methyl chloride	40-60	1,369-1,375	-	uninflamm.	2
Methylacetate	57	0,932	170	- 13	2,2
Methylene chloride	40-42	1,323	349	uninflamm.	1,8
Methylethylketone	78-85	0,820	65	+ 14	5,3
Methyl-glycol-acetate	138	1,001	7,3	+ 44	35
Methylisobutylketone	115,9	0,800	15,2	+ 14	8,7
Monoglycol acetate	178	1,109	-	+ 102	806
Mononitrobenzol	211	1,205	44,4	+ 89-90	-
Nitro thinner		0,903			
Perchloroethylene	121	1,623	14	uninflamm.	11
Pine oil	160-180	0,86-0,88	-	+ 35	-
Propyl acetate	97-102	0,887	25	+ 12	6,1
Pure spirits of turpentine	150-175	0,862	-	+ 32	-
Solvesso 100	157-180	0,88	4,1	+ 43	-
Solvesso 150	183-210	0,9	0,3	+ 66	-
Tetrachlorethane	145	1,600	5	-	33
Tetraline	205	0,975	-	+ 80	190
Toluene	109,5-110	0,884	22	+ 7	5,1
Trichlorethylene	87	1,464	56	uninflamm.	3,8
Trichloroethane	70-88	1,320	100	- 95	-
White spirit	130-180	0,70-0,82	-	+ 25,5	-
Xylene	137-139	0,854	10	+ 23	-

Distilling Units

Languages > 

EV 125 Vacuum



Distilling Unit
EV 125

Description

The EV 125 VACUUM has been manufactured acc. to the directive 89/392/EEC. Execution EExd IIBT3-IP55. The can be used for the recovery of allexhausted solvents, thinners and desiccation of residual waste. The Double-walled solvent tank and the vacuum tank are made of Chromium-Nickel-Steel acc. to DIN 1.4301. Indirectly heating by a diathermic oil. Vapor cooling by air/air exchangers.

The waste extraction and solvent tank is cleaned with a scraper that is drive by a motor. The electric vacuum pump has suction capacity of 4m³/hours. The highest vaccuum is reached at 680 mm The distilling unit is equipped with a min and max. vacuum gauge. The pneumatic pump transfers the

Technical data

Capacity	125 lt.
Heating power	9,6 kW
Cycle length h	4,5 - 8
Dimensions	210 x 102 x 252 cm
Weight	1000 kg

* Changes and mistakes excepted, prices plus packing and VAT.

Solvent distillation

Languages > 

Thinner and solvent list

THINNER AND SOLVENT	BOILING POINT °C	GRAVITY AT 20/4°C	VAPOUR TENSION AT 20°C IN mm	FLASH POINT °C	RELATIVE VOLATILITY
Aceton	56,1	0,792	178	- 17	2,1
Butyl acetate sec.	112,2	0,870	-	+ 19	12
Butyl acetate n.	126,3	0,882	10	+ 25	11,8
Butyl alcohol	117	0,810	5	+ 46	33
Butyl alcohol sec.	99,5	0,808	-	+ 24	20
Butylglycol	161-182	0,907	-	+ 60	-
Cyclohexane	81	0,783	3,1	- 12	5
Cyclohexanol	161	0,945	-	+ 68	103
Cyclohexanone	156	0,947	4	+ 54	40,4
Decalin	180-190	0,890	-	+ 57	-
Diacetonolcohol	150-165	0,938	10	+ 52	147
Dichlorethane	84-84	1,255	64	+ 21	-
Dichloropropane	96,4	1,156	36	+ 21	-
Diesel oil solvent	120-180	0,874-0,910	-	+ 22-32	-
Diethylenic glycol	240-250	1,120	-	+ 143	-
Dimethylformamide	153	0,953	3,5	+ 57	-
Dipentene	175-195	0,840-0,850	-	+ 43	-
Ethyl acetate	77	0,900	72,8	+ 2	2,9
Ethyl alcohol	78	0,840	45	+ 14	8,3
Ethyl ether	34-35	0,722	422	- 40	1
Ethylenic glycol	135	0,932	4,5	+ 40	43
Ethyl-glycol acetate	156,4	0,972	1,2	+ 49	47
Ethylsiliceous alcohol	183,5	0,830	0,05	+ 27	-
Freon 112	92,8				
Isobutyl acetate	117	0,871	12,8	+ 18	7,7
Isobutyl alcohol	107	0,805	8,8	+ 38	24
Isoforone	205-216	0,920	-	-	-
Isopropyl acetate	89,4	0,869	63	0	4,2
Isopropyl alcohol	82	0,786	32,9	+ 22	21
Methyl alcohol	65	0,725	96	+ 5,5	53
Methyl chloride	40-60	1,369-1,375	-	uninflam.	2
Methylacetate	57	0,932	170	- 13	2,2
Methylene chloride	40-42	1,323	349	uninflam.	1,8
Methylethylketone	78-85	0,820	65	+ 14	5,3
Methyl-glycol-acetate	138	1,001	7,3	+ 44	35
Methylisobutylketone	115,9	0,800	15,2	+ 14	8,7
Monoglycol acetate	178	1,109	-	+ 102	806
Mononitrobenzol	211	1,205	44,4	+ 89-90	-
Nitro thinner		0,903			
Perchloroethylene	121	1,623	14	uninflam.	11
Pine oil	160-180	0,86-0,88	-	+ 35	-
Propyl acetate	97-102	0,887	25	+ 12	6,1
Pure spirits of turpentine	150-175	0,862	-	+ 32	-
Solvesso 100	157-180	0,88	4,1	+ 43	-
Solvesso 150	183-210	0,9	0,3	+ 66	-
Tetrachlorethane	145	1,600	5	-	33
Tetraline	205	0,975	-	+ 80	190
Toluene	109,5-110	0,884	22	+ 7	5,1
Trichlorethylene	87	1,464	56	uninflam.	3,8
Trichloroethane	70-88	1,320	100	- 95	-
White spirit	130-180	0,70-0,82	-	+ 25,5	-
Xylene	137-139	0,854	10	+ 23	-

* Changes and mistakes excepted, prices plus packing and VAT.