

Schraubenkompressoren

Languages > 

Schraubenkompressor - RSKF 4,0 - RSKF 45,0



RSKF 4,0 - RSKF 45,0
Art.-Nr. 201500000305

Einsatzbereich

Schraubenkompressoren mit Kältetrockner und Frequenzregelung, konzipiert für den harten industriellen Einsatz.

Druckluft-Komplett-Station.

Kein zusätzlicher Montageaufwand für Frequenzumrichter und Kältetrockner.

Einfach elektrisch und druckseitig anschließen.

Technische Daten

Typ	Liefermenge m ³ /min				Nennleistung		Abmessungen B x T x H in mm	Gewicht kg
	7,5 bar	10 bar	13 bar	15 bar	kW	HP		
RSKF 4,0	0,17 - 0,56	0,14 - 0,46	0,10 - 0,34	0,09 - 0,30	4,0	5,5	567 x 1115 x 900	220
RSKF 5,5	0,23 - 0,77	0,20 - 0,65	0,16 - 0,53	0,14 - 0,45	5,5	7,5	567 x 1115 x 900	230
RSKF 7,5	0,33 - 1,10	0,29 - 0,95	0,22 - 0,74	0,19 - 0,63	7,5	10,0	567 x 1115 x 900	245
RSKF 9,0	–	0,33 - 1,09	0,26 - 0,86	0,23 - 0,76	9,0	12,0	567 x 1115 x 900	275
RSKF11.0	0,52 - 1,76	0,45 - 1,50	0,35 - 1,16	0,28 - 0,93	11,0	15,0	664 x 1522 x 1117	490
RSKF15.0	0,67 - 2,24	0,59 - 1,96	0,45 - 1,51	0,37 - 1,24	15,0	20,0	664 x 1522 x 1117	500
RSKF 18.5	0,87 - 2,91	0,79 - 2,62	0,66 - 2,20	0,57 - 1,89	18,5	25,0	791 x 1873 x 1290	680
RSKF 22.0	1,04 - 3,46	0,93 - 3,10	0,80 - 2,66	0,69 - 2,31	22,0	30,0	791 x 1873 x 1290	710
RSKF1-30.0	1,31 - 4,38	1,20 - 4,01	1,06 - 3,52	0,91 - 3,02	30,0	40,0	791 x 1873 x 1290	755
RSKF2-30.0	1,52 - 5,05	1,28 - 4,28	1,13 - 3,76	1,02 - 3,40	30,0	40,0	933 x 2030 x 1574	940
RSKF 37.0	1,85 - 6,15	1,57 - 5,24	1,37 - 4,56	1,25 - 4,15	37,0	50,0	933 x 2030 x 1574	990
RSKF45.0	2,18 - 7,25	1,95 - 6,51	1,67 - 5,55	1,51 - 5,03	45,0	60,0	933 x 2030 x 1574	1050

* Änderungen und Irrtümer vorbehalten, alle Preise zzgl. Verpackung und Mwst.

Screw Compressors

Languages > 

Screw Compressors - RSKF 4,0 - RSKF 45,0



RSKF 4,0 - RSKF 45,0
Art.-Nr. 201500000305

Application Area

Screw compressors with refrigeration dryer and frequency control, designed for use in tough industrial environments.

Complete compressed-air station.

No additional time spent installing frequency converters and refrigeration dryers.

Simply connect to the power and pressure systems.

Technical Data

Type	Flow Rate m ³ /min				Drive Capacity		Measurements B x T x H in mm	Weight kg
	7,5 bar	10 bar	13 bar	15 bar	kW	HP		
RSKF 4,0	0,17 - 0,56	0,14 - 0,46	0,10 - 0,34	0,09 - 0,30	4,0	5,5	567 x 1115 x 900	220
RSKF 5,5	0,23 - 0,77	0,20 - 0,65	0,16 - 0,53	0,14 - 0,45	5,5	7,5	567 x 1115 x 900	230
RSKF 7,5	0,33 - 1,10	0,29 - 0,95	0,22 - 0,74	0,19 - 0,63	7,5	10,0	567 x 1115 x 900	245
RSKF 9,0	–	0,33 - 1,09	0,26 - 0,86	0,23 - 0,76	9,0	12,0	567 x 1115 x 900	275
RSKF11.0	0,52 - 1,76	0,45 - 1,50	0,35 - 1,16	0,28 - 0,93	11,0	15,0	664 x 1522 x 1117	490
RSKF15.0	0,67 - 2,24	0,59 - 1,96	0,45 - 1,51	0,37 - 1,24	15,0	20,0	664 x 1522 x 1117	500
RSKF 18.5	0,87 - 2,91	0,79 - 2,62	0,66 - 2,20	0,57 - 1,89	18,5	25,0	791 x 1873 x 1290	680
RSKF 22.0	1,04 - 3,46	0,93 - 3,10	0,80 - 2,66	0,69 - 2,31	22,0	30,0	791 x 1873 x 1290	710
RSKF1-30.0	1,31 - 4,38	1,20 - 4,01	1,06 - 3,52	0,91 - 3,02	30,0	40,0	791 x 1873 x 1290	755
RSKF2-30.0	1,52 - 5,05	1,28 - 4,28	1,13 - 3,76	1,02 - 3,40	30,0	40,0	933 x 2030 x 1574	940
RSKF 37.0	1,85 - 6,15	1,57 - 5,24	1,37 - 4,56	1,25 - 4,15	37,0	50,0	933 x 2030 x 1574	990
RSKF45.0	2,18 - 7,25	1,95 - 6,51	1,67 - 5,55	1,51 - 5,03	45,0	60,0	933 x 2030 x 1574	1050

* Änderungen und Irrtümer vorbehalten, alle Preise zzgl. Verpackung und Mwst.

Screw Compressors

Languages > 

Screw Compressors - RSKF 4,0 - RSKF 45,0



RSKF 4,0 - RSKF 45,0
Item-No.: 201500000305

Application Area

Screw compressors with refrigerant dryer and frequency control, designed for use in tough industrial environments.

Complete compressed-air station.

No additional time spent installing frequency converters and refrigerant dryers.

Simply connect to the power and pressure systems.

Technical Data

Type	Flow Rate m ³ /min				Drive Capacity		Measurements B x T x H in mm	Weight kg
	7,5 bar	10 bar	13 bar	15 bar	kW	HP		
RSKF 4,0	0,17 - 0,56	0,14 - 0,46	0,10 - 0,34	0,09 - 0,30	4,0	5,5	567 x 1115 x 900	220
RSKF 5,5	0,23 - 0,77	0,20 - 0,65	0,16 - 0,53	0,14 - 0,45	5,5	7,5	567 x 1115 x 900	230
RSKF 7,5	0,33 - 1,10	0,29 - 0,95	0,22 - 0,74	0,19 - 0,63	7,5	10,0	567 x 1115 x 900	245
RSKF 9,0	–	0,33 - 1,09	0,26 - 0,86	0,23 - 0,76	9,0	12,0	567 x 1115 x 900	275
RSKF11.0	0,52 - 1,76	0,45 - 1,50	0,35 - 1,16	0,28 - 0,93	11,0	15,0	664 x 1522 x 1117	490
RSKF15.0	0,67 - 2,24	0,59 - 1,96	0,45 - 1,51	0,37 - 1,24	15,0	20,0	664 x 1522 x 1117	500
RSKF 18.5	0,87 - 2,91	0,79 - 2,62	0,66 - 2,20	0,57 - 1,89	18,5	25,0	791 x 1873 x 1290	680
RSKF 22.0	1,04 - 3,46	0,93 - 3,10	0,80 - 2,66	0,69 - 2,31	22,0	30,0	791 x 1873 x 1290	710
RSKF1-30.0	1,31 - 4,38	1,20 - 4,01	1,06 - 3,52	0,91 - 3,02	30,0	40,0	791 x 1873 x 1290	755
RSKF2-30.0	1,52 - 5,05	1,28 - 4,28	1,13 - 3,76	1,02 - 3,40	30,0	40,0	933 x 2030 x 1574	940
RSKF 37.0	1,85 - 6,15	1,57 - 5,24	1,37 - 4,56	1,25 - 4,15	37,0	50,0	933 x 2030 x 1574	990
RSKF45.0	2,18 - 7,25	1,95 - 6,51	1,67 - 5,55	1,51 - 5,03	45,0	60,0	933 x 2030 x 1574	1050

* Changes and mistakes excepted, prices plus packing and VAT.